

CLAIMS

What is claimed is:

1 1. A method of controlling access to content in a multimedia communication
2 network system having a plurality of access devices, the method comprising:
3 receiving configuration information related to a user object from a user via an
4 access device of the plurality of access devices, the configuration information
5 defining multimedia content that can be accessed by instantiating the user object in
6 an access device; and
7 providing the received configuration information to another access device of
8 the plurality of access devices.

1 2. The method of claim 1, further comprising receiving revised configuration
2 information related to the user object via an access device of the plurality of access
3 devices and providing the received revised configuration information to all of the
4 access devices of the plurality of access devices.

1 3. The method of claim 1, further comprising receiving configuration information
2 related to a plurality of user objects via one or more of the access devices of the
3 plurality of access devices and providing the configuration information to all of the
4 access devices of the plurality of access devices.

1 4. The method of claim 3, further comprising assigning a ticket number to the
2 revised configuration information.

1 5. The method of claim 4, further comprising storing the ticket number in a
2 revision history in the multimedia communication network system.

1 6. The method of claim 5, wherein the revision history is stored in a server of the
2 multimedia communication network system.

1 7. A control system of controlling access to content in a multimedia
2 communication network system having a plurality of access devices, the control
3 system comprising:

4 means for receiving configuration information related to a user object from a
5 user via an access device of the plurality of access devices, the configuration
6 information defining multimedia content that can be accessed by instantiating the
7 user object in an access device; and

8 means for providing the received configuration information to another access
9 device of the plurality of access devices.

1 8. The control system of claim 7, further comprising means for receiving revised
2 configuration information related to the user object via an access device of the
3 plurality of access devices and for providing the received revised configuration
4 information to all of the access devices of the plurality of access devices.

1 9. The control system claim 7, further comprising means for receiving
2 configuration information related to a plurality of user objects via one or more of the
3 access devices of the plurality of access devices and for providing the configuration
4 information to all of the access devices of the plurality of access devices.

1 10. The control system of claim 9, further comprising means for assigning a ticket
2 number to the revised configuration information.

1 11. The control system of claim 10, further comprising a revision history for
2 storing the ticket number.

1 12. The control system of claim 11, wherein the revision history is stored in a
2 server of the multimedia communication network system.

1 13. A machine-readable medium for use in a multimedia communication network
2 having a plurality of access devices, the machine-readable medium containing
3 instructions, the instructions when executed by a machine cause the machine to
4 perform operations comprising:

5 receiving configuration information related to a user object from a user via an
6 access device of the plurality of access devices, the configuration information
7 defining multimedia content that can be accessed by instantiating the user object in
8 an access device; and

9 providing the received configuration information to another access device of
10 the plurality of access devices.

1 14. The machine-readable medium of claim 13, wherein the operations further
2 comprise receiving revised configuration information related to the user object via an
3 access device of the plurality of access devices and providing the received revised
4 configuration information to all of the access devices of the plurality of access
5 devices.

1 15. The machine-readable medium of claim 13, wherein the operations further
2 comprise receiving configuration information related to a plurality of user objects via
3 one or more of the access devices of the plurality of access devices and providing
4 the configuration information to all of the access devices of the plurality of access
5 devices.

1 16. The machine-readable medium of claim 13, wherein the operations further
2 comprise assigning a ticket number to the revised configuration information.

1 17. The machine-readable medium of claim 16, wherein the operations further
2 comprise storing the ticket number in a revision history stored in the machine-
3 readable medium.

1 18. A method of providing configuration information related to user object of a
2 multimedia communication network system having a plurality of access devices, the
3 configuration information including values for a plurality of configuration parameters,
4 the method comprising:

5 receiving a portion of the configuration information related from a user via an
6 access device of the plurality of access devices;

7 assigning a ticket number to the received portion of the configuration
8 information;

9 storing the ticket number in a revision history; and

10 providing the ticket number to the access device.

1 19. The method of claim 18, further comprising:

2 setting a bit in a bit vector, the bit vector having a plurality of bits each being
3 associated to a corresponding configuration parameter of the user object; wherein
4 the set bit indicates the configuration parameter associated with the received
5 configuration information; and
6 providing the bit vector to the access device.

1 20. The method of claim 18, wherein the revision history has a fixed size.

1 21. The method of claim 18, further comprising providing the portion of the
2 configuration information to a second access device of the plurality of access
3 devices.

1 22. An update system for providing configuration information related to user
2 object of a multimedia communication network system having a plurality of access
3 devices and a revision history, the configuration information including values for a
4 plurality of configuration parameters, the method comprising:

5 means for receiving a portion of the configuration information related from a
6 user via an access device of the plurality of access devices;

7 means for assigning a ticket number to the received portion of the
8 configuration information;

9 means for storing the ticket number in the revision history; and

10 providing the ticket number to the access device.

1 23. The update system of claim 22, further comprising:

2 means for setting a bit in a bit vector, the bit vector having a plurality of bits
3 each being associated to a corresponding configuration parameter of the user

4 object; wherein the set bit indicates the configuration parameter associated with the
5 received configuration information; and
6 means for providing the bit vector to the access device.

1 24. The update system of claim 22, wherein the revision history has a fixed size.

1 25. The update system of claim 22, further comprising means for providing the
2 portion of the configuration information to a second access device of the plurality of
3 access devices.

1 26. A machine-readable medium for use in a multimedia communication network
2 system having a plurality of access devices, the configuration information including
3 values for a plurality of configuration parameters, the machine-readable medium
4 containing instructions which, when executed by an apparatus, cause the apparatus
5 to perform operations comprising:

6 receiving a portion of the configuration information related from a user via an
7 access device of the plurality of access devices;

8 assigning a ticket number to the received portion of the configuration
9 information;

10 storing the ticket number in a revision history; and

11 providing the ticket number to the access device.

1 27. The machine-readable medium of claim 26, wherein the operations further
2 comprise:

3 setting a bit in a bit vector, the bit vector having a plurality of bits each being
4 associated to a corresponding configuration parameter of the user object; wherein

5 the set bit indicates the configuration parameter associated with the received
6 configuration information; and
7 providing the bit vector to the access device.

1 28. The machine-readable medium of claim 26, wherein the revision history has a
2 fixed size.

1 29. The machine-readable medium of claim 26, wherein the operations further
2 comprise providing the portion of the configuration information to a second access
3 device of the plurality of access devices.

1 30. A method of providing updated configuration information related to user
2 object of a multimedia communication network system having a plurality of access
3 devices, the configuration information including values for a plurality of configuration
4 parameters, the system including a revision history configured to store identifiers
5 and bit vectors associated with updates to the configuration information related to
6 the user object, the method comprising:

7 receiving an identifier from an access device of the plurality of access
8 devices;

9 determining an update vector as a function of the received identifier and any
10 identifiers in the revision history that are more recent than the ticket number; and

11 providing the update vector to the access device.

1 31. The method of claim 30, further comprising providing a portion of updated
2 configuration information to the access device at the request of the access device,
3 wherein the access generates the request in response to the update vector.

1 32. The method of claim 30, further comprising providing to the access device the
2 most recent identifier of the identifiers used in determining the update vector.

1 33. The method of claim 30, wherein determining the update vector further
2 comprises generating the update vector as a function of the bit vectors associated
3 with the identifiers that are more recent than the received identifier.

1 34. The method of claim 33, wherein the function of the bit vectors comprises the
2 logical-OR of the bit vectors associated with the identifiers that are more recent than
3 the received identifier.

1 35. A machine-readable medium for use in a multimedia communication network
2 system having a plurality of access devices, the configuration information including
3 values for a plurality of configuration parameters, the system including a revision
4 history configured to store identifiers and bit vectors associated with updates to the
5 configuration information related to the user object, the machine-readable medium
6 providing instructions that when executed by a machine cause the machine to
7 perform operations comprising:

8 receiving an identifier from an access device of the plurality of access
9 devices;

10 determining an update vector as a function of the received identifier and any
11 identifiers in the revision history that are more recent than the ticket number; and

12 providing the update vector to the access device.

1 36. The machine-readable medium of claim 35, wherein the operations further
2 comprise providing a portion of updated configuration information to the access
3 device at the request of the access device, wherein the access generates the
4 request in response to the update vector.

1 37. The machine-readable medium of claim 35, wherein the operations further
2 comprise providing to the access device the most recent identifier of the identifiers
3 used in determining the update vector.

1 38. The machine-readable medium of claim 35, wherein the operation of
2 determining the update vector further comprises an operation of generating the
3 update vector as a function of the bit vectors associated with the identifiers that are
4 more recent than the received identifier.

1 39. The machine-readable medium of claim 38, wherein the function of the bit
2 vectors comprises the logical-OR of the bit vectors associated with the identifiers
3 that are more recent than the received identifier.

1 40. An update system for providing updated configuration information related to
2 user object of a multimedia communication network system having a plurality of
3 access devices, the configuration information including values for a plurality of
4 configuration parameters, the multimedia communication network system including
5 a revision history configured to store identifiers and bit vectors associated with
6 updates to the configuration information related to the user object, the update
7 system comprising:

8 means for receiving an identifier from an access device of the plurality of
9 access devices;

10 means for determining an update vector as a function of the received
11 identifier and any identifiers in the revision history that are more recent than the
12 ticket number; and

13 means for providing the update vector to the access device.

1 41. The update system of claim 40, further comprising means for providing to the
2 access device the most recent identifier of the identifiers used by the means for
3 determining in determining the update vector.

1 42. The update system of claim 40, further comprising means for providing a
2 portion of updated configuration information to the access device at the request of
3 the access device, wherein the access generates the request in response to the
4 update vector.

1 43. The update system of claim 40, wherein the means for determining the
2 update vector further comprises means for generating the update vector as a
3 function of the bit vectors associated with the identifiers that are more recent than
4 the received identifier.

1 44. The update system of claim 43, wherein the function of the bit vectors
2 comprises the logical-OR of the bit vectors associated with the identifiers that are
3 more recent than the received identifier.